



PHR-4017V

8路电压输入模块

- 分辨率:16位
- 通道数:8路电压
- 输入信号类型: $\pm 150\text{mV}$ 、 $\pm 500\text{mV}$ 、 $\pm 1\text{V}$ 、 $\pm 5\text{V}$ 、 $\pm 10\text{V}$ 数据更新速率:250ms
- 采样频率:10Hz
- 精度:0.1%F.S(典型值为0.05%F.S)
- 温度漂移:0.005%FS/ $^{\circ}\text{C}$
- 供电电源:18~30VDC
- 最大功耗:1.2W/24VDC
- 隔离电压:3000VDC
- 工作温度: $-20^{\circ}\text{C}\sim 70^{\circ}\text{C}$
- 存储温度: $-40^{\circ}\text{C}\sim 85^{\circ}\text{C}$
- 湿度:5%~90%,无凝露

PHR-4017V

8 channel voltage input module

- Resolution: 16 bit
- Channel number: 8 channel voltage
- Input signal type: $\pm 150\text{V}$ 、 $\pm 500\text{mN}$ 、 $\pm 1\text{V}$ 、 $\pm 5\text{V}$ 、 $\pm 10\text{V}$
- Data update rate: 250ms
- Sampling frequency: 10Hz
- Accuracy: 0.1 ‰ F.S (typical value is 0.05% F.S)
- Temperature drift: 0.005% F.S / $^{\circ}\text{C}$
- Power supply: 18 ~ 30VDC
- Maximum power consumption: 1.2W/24VDC
- Isolation voltage: 3000VDC
- Working temperature: $- 20^{\circ}\text{C} \sim 70^{\circ}\text{C}$
- Storage temperature: $- 40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
- Humidity: 5% ~ 90%, no condensation